



FORESTRY - GUIDE BARS

DURA TIP BAR

A tough Cobalt tipped solid bar that is designed for the most severe and abrasive cutting conditions. This bar has the best durability and extended life under these harsh conditions.



| Product Code | Length | | Pitch Inch | Gauge | | No. of Drivelinks | Product Code | Length | | Pitch Inch | Gauge | | No. of Drivelinks |
|--------------|--------|----|------------|-------|------|-------------------|--------------|--------|------|------------|-------|------|-------------------|
| | inch | cm | | mm | inch | | | inch | inch | | cm | mm | |
| 16CJL50 | 16 | 40 | .325 | 1.3 | .050 | 66 | 25WZ63 | 25 | 60 | .404 | 1.6 | .063 | 84 |
| 16TMX50 | 16 | 40 | 3/8 | 1.3 | .050 | 60 | 254050 | 25 | 60 | 3/8 | 1.3 | .050 | 84 |
| 16UXL50 | 16 | 40 | 3/8 | 1.3 | .050 | 60 | 254063 | 25 | 60 | 3/8 | 1.6 | .063 | 84 |
| 164050 | 16 | 40 | 3/8 | 1.3 | .050 | 60 | 28HU58 | 28 | 70 | 3/8 | 1.5 | .058 | 92 |
| 164063 | 16 | 40 | .325 | 1.6 | .063 | 67 | 28HU63 | 28 | 70 | 3/8 | 1.6 | .063 | 92 |
| 170763 | 17 | 43 | .404 | 1.6 | .063 | 60 | 30WZ63 | 30 | 75 | .404 | 1.6 | .063 | 92 |
| 18CJL50 | 18 | 45 | 3/8 | 1.3 | .050 | 68 | 33WZ63 | 33 | 83 | .404 | 1.6 | .063 | 100 |
| 18CJL58 | 18 | 45 | .325 | 1.5 | .058 | 72 | 34HU63 | 34 | 85 | .404 | 1.6 | .063 | 100 |
| 18HU58 | 18 | 45 | 3/8 | 1.5 | .058 | 68 | 36HU63 | 36 | 90 | .404 | 1.6 | .063 | 104 |
| 184063 | 18 | 45 | .325 | 1.6 | .063 | 74 | 36WZ63 | 36 | 90 | .404 | 1.6 | .063 | 104 |
| 20CJL50 | 20 | 50 | .325 | 1.3 | .050 | 78 | 42WZ63 | 42 | 105 | .404 | 1.6 | .063 | 124 |
| 20HU50 | 20 | 50 | 3/8 | 1.3 | .050 | 72 | | | | | | | |
| 20HU58 | 20 | 50 | 3/8 | 1.5 | .058 | 72 | | | | | | | |
| 20HU63 | 20 | 50 | 3/8 | 1.6 | .063 | 72 | | | | | | | |
| 20TMX50 | 20 | 50 | 3/8 | 1.3 | .050 | 70 | | | | | | | |
| 20UXL50 | 20 | 50 | 3/8 | 1.3 | .050 | 70 | | | | | | | |
| 210763 | 21 | 50 | .404 | 1.6 | .063 | 68 | | | | | | | |
| 214050 | 21 | 50 | 3/8 | 1.3 | .050 | 72 | | | | | | | |
| 214063 | 21 | 50 | 3/8 | 1.6 | .063 | 72 | | | | | | | |
| 24HU50 | 24 | 60 | 3/8 | 1.3 | .050 | 84 | | | | | | | |
| 24HU58 | 24 | 60 | 3/8 | 1.5 | .058 | 84 | | | | | | | |
| 24HU63 | 24 | 60 | 3/8 | 1.6 | .063 | 84 | | | | | | | |